

HENKEL CONSUMER ADMESIVES
50 WEST DRIVE
BRAMPTON, ONTARIO CANADA L6T 2J4
(905) 459-1140

PRODUCT : LOCTITE FABRIC GLUE



SECTION 01: PRODUCT INFORMATION

MANUFACTURER.....LOCTITE CORPORATION

1001 TROUT BROOK CROSSING ROCKY HILL, COMMECTICUT U.S.A., 06067-3910 (860) 571-5100;

AFTER HOURS - CANUTEC (613) 996-6666

DISTRIBUTOR...... HEWKEL CONSUMER ADRESIVES, 50 WEST DRIVE, BRAMPTON, ON L6T 2J4 CANADA.

(905) 459-1140: CANUTEC: (613) 996-6666

WHMIS CLASSIFICATION..................D2B. WHEN THIS PRODUCT IS LABELLED AS A CONSUMER PRODUCT IT IS EXEMPT FROM

WHMIS REGULATIONS. (SEE SECTION 12(f) OF THE HAZARDOUS PRODUCTS ACT).

T.D.G. CLASSIFICATION......NOT REGULATED
PRODUCT NAME......LOCTITE FABRIC GLUE
CHEMICAL FAMILY.....ACRYLIC RESINS
MATERIAL USE......ADHESIVE. SEALART

SECTION 02: HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	*	EXPOSURE LEVELS	C.A.S. #	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES
Ethanol	1-5	TLV-TWA: 1000 ppm	64-17-5	7.1g/kg,oral,rat	20000ppm/10hr. rat
Free ammonia	0.1-1	TLV: 50 ppm 8hrTWA PEL: 25 ppm 8hrTWA		Not available	Not svailable
Sodium lauryl sulfate	0.1-1	Not available	151-21-3	1.3g/kg,oral,rat	Not available

SECTION 03: PHYSICAL DATA

PHYSICAL STATE......Paste

BY VOLUME

BY WEIGHT

BOILING POINT (deg C)Approx. 100 deg C

DISTRIBUTION

SECTION 04: FIRE & EXPLOSION DATA

IF YES, UNDER WHICH

CONDITIONS?

AUTO IGNITION TEMPERATURE......Not available

EXTINGUISHING MEDIA......Dry chemical. CO2. Foam

SPECIAL PROCEDURES...... fire fighters should be equipped with self-contained breathing apparatus

to protect against potentially toxic and irritating fumes.

FLASH POINT (C), METHOD..... 93 deg C, TCC

LOWER FLAMMABLE LIMIT (% VOL) 16 % (ammonia). 3.3 % (ethyl alcohol)

UPPER FLAMMABLE LIMIT (% VOL) 25 % (ammonia) . 19 % (ethyl alcohol)

SENSITIVITY TO IMPACT..... No

DISCHARGE

HAZARDOUS COMBUSTION PRODUCTS....Acrylic monomers. Ammonia. Oxides of carbon (CO,CO2)

SECTION 05: REACTIVITY DATA

CHEMICAL STABILITY:

YES..... Stable under normal temperature and pressure.

NO, WHICH CONDITIONS ?

01062003 MATERIAL SAFETY DATA SHEET: 00000656 PAGE:2

PRODUCT : LOCTITE FABRIC GLUE

SECTION 05: REACTIVITY DATA

COMPATIBILITY WITH OTHER

YES

NO, WHICH ONES?......Acids. Oxidizing agents

REACTIVITY CONDITIONS ?......None

HAZARDOUS PRODUCTS OF......Ammonia. Sulfur dioxide. Hydrogen sulphide. Sulfuric acid

DECOMPOSITION

SECTION 06: TOXICOLOGICAL PROPERTIES

EYE CONTACT......Slightly irritating but does not cause eye tissue damage.

eyes and the respiratory tract. Inhalation may cause irritation to the nasal passages and/or the respiratory system.

INGESTION...... May cause mild irritation of the gastrointestinal tract, nausea, womiting

and perhaps, central nervous system depression.

EFFECTS OF ACUTE EXPOSURE......Skin, eye, and respiratory tract irritation.

EFFECTS OF CHROMIC EXPOSURE.....May aggravate existing eye, skin, and lung conditions.

LD 50 OF MATERIAL, SPECIES &..... > 2 g/kg, rabbit, dermal. > 5 g/kg, oral, rat (estimated)

ROUTE

LC 50 OF MATERIAL, SPECIES &..... Refer to hazardous ingredients section.

ROUTE

EXPOSURE LIMIT OF MATERIAL......See hazardous ingradients section (2)

IRRITANCY OF MATERIAL......Refer to route of entry

SENSITIZING CAPABILITY OF......May cause allergic skin reaction, especially on prolonged or repeated

MATERIAL contact.

CARCINOGENICITY OF MATERIAL.....Not available

MUTAGENICITY OF MATERIAL......Not available TERATOGENICITY OF MATERIAL......Not available

SYMERGISTIC MATERIALS...... Not available

SECTION 07: PREVENTATIVE MEASURES

GLOVES/ TYPE.......Chemical resistant gloves.

RESPIRATORY/TYPE...........Use a MIOSH/MSHA approved respirator whenever mist or spray is generated.

Avoid prolonged or repeated breathing of vapour or mists.

EYE/TYPE......Safety glasses with side-shields

FOOTWEAR/TYPE......Standard work shoes.

CLOTHING/TYPE......Standard work clothes.

Scrape or shovel into containers. Put in appropriate labelled container

for disposal. Wash spill area with soap and water.

emptied container retains product residues all labelled hazard precautions

must be observed.

HANDLING PROCEDURES AND........use adequate ventilation. Avoid breathing vapours. Avoid skin and eye

EQUIPMENT contact. Avoid smoking, drinking or eating in use. Wash thoroughly after handling.

STORAGE MEEDS......Store below 25 deg C. Protect from freezing in storage and transit.

SPECIAL SHIPPING INSTRUCTIONS....Not regulated

SECTION 08: FIRST AID MEASURES

EYE CONTACT..... of 15 minutes holding lids

apart to ensure flushing of entire surface. Washing within 1 minute is

essential to achieve maximum effectiveness. Seek medical attention

immediately.

airway clear. Get medical attention. Mever give anything by mouth to an

unconscious person. Get immediate medical attention

medical attention if irritation occurs or persists.

SECTION 09: PREPARATION INFORMATION

TELEPHONE NUMBER:.....(905) 459-1140

01062003

MATERIAL SAFETY DATA SHEET : 00000656

PAGE: 3

PRODUCT : LOCTITE FABRIC GLUE

SECTION 09: PREPARATION INFORMATION

DISCLAIMER2:..... and suggestions appearing herein concerning our product are based upon tests and data believed to be reliable. However, it is the user's responsibility to determine the safety, toxicity, and suitability for his own use of the product described herein. Since the actual use by others is beyond our control, no guarantee, express or implied, is made by Henkel Consumer Adhesives as to the effects of such use, the results obtained, or the safety and toxicity of the product nor does Henkel Consumer Adhesives assume any liability arising out of use, by others, of the product referred to herein. The information herein is not to be construed as absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstan ces exist or because of applicable laws or government regulations.

PREPARATION DATE......JUN 21/2002

CANUTEC EMERGENCY (613) 996-6666